



MSI Graphics Card Quick Start Guide



Installation Guide
[NVIDIA]



Installation Guide
[AMD]



條文碼位置
Part NO: GS2-XXXXGE2



MSI Afterburner is the world's most recognized and
widely used graphics card overclocking utility.
For more information please visit:
<http://www.msi.com/page/afterburner>



The terms HDMI™, HDMI™ Logo, Definition
Multimedia Interface, HDMI™ Logo and
the HDMI™ Logo are trademarks of
registered owners of HDMI Licensing
Administration, Inc.

• Note that the installation pictures shown here are for reference
only and may vary from the actual ones.
• For more information about MSI Graphics Cards, please visit
MSI website at www.msi.com/graphics-cards

Package Contents

1. MSI Graphics Card
2. MSI Graphics Card Bracket

System Requirements

1. Windows 10/11
2. DirectX 12
3. Windows

Auxiliary Tools

1. Screwdriver

Hardware Installation

1. Remove the backplate from the graphics card.
2. Insert the graphics card into the PCIe slot.
3. Secure the graphics card with the bracket.
4. Connect the power cables to the graphics card.
1. Connect the power cables to the graphics card.
2. Connect the signal cables to the graphics card.
3. Connect the monitor to the graphics card.
4. Turn on the power and test the system.
1. Connect the power cables to the graphics card.
2. Connect the signal cables to the graphics card.
3. Connect the monitor to the graphics card.
4. Turn on the power and test the system.
1. Connect the power cables to the graphics card.
2. Connect the signal cables to the graphics card.
3. Connect the monitor to the graphics card.
4. Turn on the power and test the system.

Polski

Zawartość opakowania

1. Karta graficzna MSI
2. Klamra zabezpieczająca kartę graficzną MSI

Wymagania systemowe

1. Windows 10/11
2. DirectX 12
3. Windows

Narzędzia pomocnicze

1. Śrubokręt

Instalacja sprzętu

1. Wyjmij tył karty graficznej z tyłu obudowy komputera.
2. Włóż kartę graficzną do gniazda PCIe.
3. Zamocuj kartę graficzną klamrą.
4. Podłącz przewody zasilające do karty graficznej.
5. Podłącz przewody sygnałowe do karty graficznej.
6. Podłącz monitor do karty graficznej.
7. Włącz komputer i sprawdź, czy wszystko działa.