


Kodak PIXPRO

Digital Cameras

SPZ1 DIGITAL CAMCORDER



FEATURES:

Mother nature has met her match with the new rugged, SPZ1 Digital Camcorder. Take this 1080p HD video camera anywhere you want. Its easy one touch record, 3X optical zoom and plenty of megapixels give you sharp, clear photos and HD video no matter how extreme your adventure. KODAK PIXPRO Digital Cameras. Tell your story.

- 5m Waterproof
- 1.5m Shockproof
- Dustproof, Freezeproof
- Full HD 1080p Video
- 14MP CMOS
- 5 fps Burst Shooting
- 360° Panorama



Available Colors: 

3X
OPTICAL
ZOOM


14MP
CMOS


5m
16ft
Waterproof


1.5m/5ft
Shockproof


1080p
FULL HD


360°
Panorama

Kodak

PIXPRO SPZ1

Digital Camcorder

3X
OPTICAL
ZOOM

14 MP
CMOS

5m
16ft
Waterproof

1.5m/5ft
Shockproof

1080p
FULL HD

360°
Panorama

SPECIFICATIONS

SPZ1

Effective Image Sensor Pixels	14.41 Megapixels
Total Image Sensor Pixels	15.40 Megapixels [1/2.3" CMOS]
Lens	
Focal Length [35mm film equivalent]	6.0 mm (Wide) — 18.0 mm (Tele) [35 mm (Wide) — 105 mm (Tele)]
F number	F2.8 (Wide) — F4.6 (Tele)
Lens Construction	9 groups 10 elements
Optical Zoom	3x
Focusing Range	Normal: (Wide) 60 cm — ∞, (Tele) 100 cm — ∞ Macro: 10 cm — ∞ (Wide Only)
Anti-Handshake	Video Image Stabilization
Digital Zoom	6x Digital Zoom (Combined Zoom: 18x)
Number of Recording Pixels	
Still Image	(4:3) 14MP: 4320x3240, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 12MP: 4320x2880, (16:9) 10MP: 4320x2432, 2MP: 1920x1080
Movie	1920x1080 (30fps), 1440x1080 (30fps), 1280x720 (60 fps), 1280x720 (30 fps), 640x640 (30fps), 320x240 (30 fps) High-Speed Movie: 640x480 (120 fps)
Dual Record	The resolution of still photo captured while video recording is same as video resolution
Image Compression	Best, Fine, Normal
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	Movie Format: MOV (H.264), Audio: Linear PCM (Stereo)
Shooting Modes	Auto
Detection Features	Face, Smile, Blink
High Dynamic Range (HDR)	Yes (Post-Processing)
Panorama	0° - 360°
Waterproof	Up to 16.4 ft. / 5m
Shockproof	Up to 4.9 ft. / 1.5m
Dustproof	Equivalent to JIS/IEC (IP6X)
Freezeproof	14°F / -10°C
LCD Display	2.5 inch (230K Pixels)
ISO Sensitivity	Auto, ISO 100/200/400/800/1600/3200
AF Method	Single AF, Multi-AF (TTL 9-point), Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available)
Shutter Speed	1/2000 - 1/4 Seconds
Continuous Shooting	Approx. 5fps (Full Resolution)
Playback Modes	Single Photo, Index, Slide Show, Date, Zoom (Approx. x4), FF & REW 2x/4x/8x/16x & Each Frame
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Incandescent, Underwater
Recording Media	Internal Memory: Approx. 8MB Micro SD/Micro SDHC Card (Up to 32GB Support) [MMC Card not supported]
Other Features	Multi-Language Support (27 Languages)
Jacks	USB 2.0 (Micro 5 pin USB), HDMI (Type D)
Power	Rechargeable Li-ion Battery LB-050, 3.7V 900mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 250 Shots (Based on CIPA Standards); Approx. 70 min. for Video (@1080p/30fps)
Operation Environment	Temperature: 14° - 104°F / -10° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 2.23 x 4.36 x 0.86 in / 56.6 x 110.6 x 21.7 mm (Based on CIPA Standards)
Weight	Approx. 4.6 oz. / 130g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, AC Adapter, USB Cable, Wrist Strap, CD-ROM, Quick Start Guide, Warranty Card, Service Card

JK Imaging Ltd.

JK Imaging, Ltd.
1411 W. 190th Street, Suite 550
Gardena, CA 90248

To learn more about KODAK PIXPRO Digital Cameras:
visit: www.kodakcamera.jkilt.com

